



# Synthetic Power Steering Fluid for European and Asian vehicles

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 10/26/2015

Revision date: 08/31/2018

Supersedes: 07/17/2018

Version: 1.8

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : Synthetic Power Steering Fluid for European and Asian vehicles  
Product code : 5715

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Power steering fluid

#### 1.3. Supplier

Bardahl Manufacturing Corporation  
1400 NW 52nd Street  
P.O. Box 70607  
Seattle, WA 98107  
T 206-783-4851 - F 206-784-3219  
[jackie.leung@bardahl.com](mailto:jackie.leung@bardahl.com) - [www.bardahl.com](http://www.bardahl.com)

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Not classified

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labelling

No labelling applicable

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
1-Decene, homopolymer, hydrogenated	(CAS-No.) 68037-01-4	50 - 80	Asp. Tox. 1, H304
HVI 450 Neutral Base Oil	(CAS-No.) 68476-77-7	5 - 10	Not classified
bis(tridecyl) adipate	(CAS-No.) 16958-92-2	5 - 10	Not classified
HT 150N base oil	(CAS-No.) 68476-77-7	1 - 5	Not classified
Mineral Oil	(CAS-No.) 64742-55-8	1 - 5	Not classified
Mineral oil	(CAS-No.) Mixture	0.1 - 5	Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

# Synthetic Power Steering Fluid for European and Asian vehicles

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.2. Most important symptoms and effects (acute and delayed)

No additional information available

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water spray.

### 5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

Handling temperature : 70 °C maximum.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

Storage temperature : 45 °C maximum.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 1-Decene, homopolymer, hydrogenated (68037-01-4)

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Inhalable fraction)
-------	--------------------------------	--

#### bis(tridecyl) adipate (16958-92-2)

Not applicable

#### HVI 450 Neutral Base Oil (68476-77-7)

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
-------	--------------------------------	---------------------

#### Mineral Oil (64742-55-8)

Not applicable

#### HT 150N base oil (68476-77-7)

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
-------	--------------------------------	---------------------

# Synthetic Power Steering Fluid for European and Asian vehicles

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Mineral oil (Mixture)

Not applicable

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber
Odour	: characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 200 °C minimum per COC method.
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.828 typical
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 36.2 mm <sup>2</sup> /s @ 40 C typical
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

# Synthetic Power Steering Fluid for European and Asian vehicles

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Oxidizing agent.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### HVI 450 Neutral Base Oil (68476-77-7)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

#### HT 150N base oil (68476-77-7)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified  
Viscosity, kinematic : 36.2 mm<sup>2</sup>/s @ 40 C typical

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

### 12.2. Persistence and degradability

#### 1-Decene, homopolymer, hydrogenated (68037-01-4)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

### 12.3. Bioaccumulative potential

#### 1-Decene, homopolymer, hydrogenated (68037-01-4)

Log Pow	> 6 (Calculated)
---------	------------------

### 12.4. Mobility in soil

# Synthetic Power Steering Fluid for European and Asian vehicles

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 1-Decene, homopolymer, hydrogenated (68037-01-4)

Ecology - soil

Adsorbs into the soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Not applicable

### Transportation of Dangerous Goods

Not applicable

### Transport by sea

Not applicable

### Air transport

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### 1-Decene, homopolymer, hydrogenated (68037-01-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### bis(tridecyl) adipate (16958-92-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### HVI 450 Neutral Base Oil (68476-77-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Mineral Oil (64742-55-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### HT 150N base oil (68476-77-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Mineral oil (Mixture)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

# Synthetic Power Steering Fluid for European and Asian vehicles

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

Component	State or local regulations
1-Decene, homopolymer, hydrogenated(68037-01-4)	
bis(tridecyl) adipate(16958-92-2)	
HVI 450 Neutral Base Oil(68476-77-7)	
HT 150N base oil(68476-77-7)	
Mineral Oil (64742-55-8)	
Mineral oil(Mixture)	

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 08/31/2018


Full text of H-statements:

H304	May be fatal if swallowed and enters airways.
------	---

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : B  
B - Safety glasses, Gloves

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*