



# Transmission Stop Leak

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/18/2015

Revision date: 11/02/2016

Supersedes: 09/30/2016

Version: 1.4

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Transmission Stop Leak  
Product code : 6018  
Other means of identification : 6018, 6018-4, 6018-55, 6019

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Lubricants, Greases and Release Products

#### 1.3. Details of the supplier of the safety data sheet

Bardahl Manufacturing Corporation  
1400 NW 52nd Street  
Seattle, WA 98107  
T 206-783-4851 - F 206-784-3219  
[jackie.leung@bardahl.com](mailto:jackie.leung@bardahl.com) - [www.bardahl.com](http://www.bardahl.com)

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

|   |   |
|---|---|
| Sensitisation — Skin, Category 1                                  | May cause an allergic skin reaction               |
| Reproductive toxicity, Category 1B                                | May damage fertility or the unborn child          |
| Hazardous to the aquatic environment — Acute Hazard, Category 3   | Harmful to aquatic life                           |
| Hazardous to the aquatic environment — Chronic Hazard, Category 3 | Harmful to aquatic life with long lasting effects |

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

May cause an allergic skin reaction  
May damage fertility or the unborn child  
Harmful to aquatic life  
Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Avoid breathing mist, vapours  
Contaminated work clothing must not be allowed out of the workplace  
Avoid release to the environment  
Wear protective gloves, eye protection  
If on skin: Wash with plenty of water  
If exposed or concerned: Get medical advice/attention  
Specific treatment (see supplemental first aid instruction on this label)  
If skin irritation or rash occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
Store locked up  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

# Transmission Stop Leak

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name  | Product identifier  | %        | GHS-US classification  |
|---|---------------------|----------|--|
| 150 Neutral Base Oil<br>substance with OEL values | (CAS No) 64742-58-1 | >= 80    | Not classified   |
| Mineral oil                                       | (CAS No) 64742-53-6 | 1 - 5    | Asp. Tox. 1, H304  |
| Glycol Ether DPM                                  | (CAS No) 34590-94-8 | 1 - 5    | Flam. Liq. 4, H227<br>Repr. 1B, H360   |
| Arylamine   | (CAS No) 90-30-2    | 0.01 - 1 | Acute Tox. 4 (Oral), H302<br>Skin Sens. 1, H317<br>STOT RE 2, H373<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410   |
| Toluene<br>substance with OEL values              | (CAS No) 108-88-3   | < 0.1    | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>STOT RE 2, H373<br>Asp. Tox. 1, H304   |
| Xylene<br>substance with OEL values               | (CAS No) 1330-20-7  | < 0.01   | Flam. Liq. 3, H226<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Skin Irrit. 2, H315  |
| Ethylbenzene<br>substance with OEL values         | (CAS No) 100-41-4   | < 0.01   | Flam. Liq. 2, H225<br>Acute Tox. 4 (Inhalation), H332<br>Acute Tox. 4 (Inhalation:dust,mist),<br>H332<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Aquatic Acute 2, H401 |

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.
- Symptoms/injuries after skin contact : May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# Transmission Stop Leak

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing mist, vapours.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing mist, vapours.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| Glycol Ether DPM (34590-94-8)     |                                     |  |
|-----------------------------------|-------------------------------------|--|
| ACGIH                             | ACGIH TWA (ppm)                     | 100 ppm (2-Methoxymethylethoxy)propanol(DPGME); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value |
| ACGIH                             | ACGIH STEL (ppm)                    | 150 ppm (2-Methoxymethylethoxy)propanol(DPGME); USA; Short time value; TLV - Adopted Value                         |
| OSHA                              | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 600 mg/m <sup>3</sup>  |
| OSHA                              | OSHA PEL (TWA) (ppm)                | 100 ppm  |
| Mineral oil (64742-53-6)          |                                     |  |
| Not applicable                    |                                     |  |
| Arylamine (90-30-2)               |                                     |  |
| Not applicable                    |                                     |  |
| 150 Neutral Base Oil (64742-58-1) |                                     |  |
| ACGIH                             | ACGIH TWA (mg/m <sup>3</sup> )      | 5 mg/m <sup>3</sup>  |
| Not applicable                    |                                     |  |
| Xylene (1330-20-7)                |                                     |  |
| ACGIH                             | ACGIH TWA (ppm)                     | 100 ppm  |
| ACGIH                             | ACGIH STEL (ppm)                    | 150 ppm  |
| ACGIH                             | Remark (ACGIH)                      | URT & eye irr; CNS impair  |
| OSHA                              | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 435 mg/m <sup>3</sup>  |
| OSHA                              | OSHA PEL (TWA) (ppm)                | 100 ppm  |

# Transmission Stop Leak

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Ethylbenzene (100-41-4) |                                     |                                   |
|-------------------------|-------------------------------------|-----------------------------------|
| ACGIH                   | ACGIH TWA (ppm)                     | 20 ppm                            |
| ACGIH                   | Remark (ACGIH)                      | URT irr; kidney dam (nephropathy) |
| OSHA                    | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 435 mg/m <sup>3</sup>             |
| OSHA                    | OSHA PEL (TWA) (ppm)                | 100 ppm                           |
| Toluene (108-88-3)      |                                     |                                   |
| ACGIH                   | ACGIH TWA (ppm)                     | 20 ppm                            |
| ACGIH                   | Remark (ACGIH)                      | Visual impair; female repro;      |
| OSHA                    | Remark (OSHA)                       | (2) See Table Z-2.                |

### 8.2. Exposure controls

|                                  |  |
|----------------------------------|--|
| Appropriate engineering controls | : Ensure good ventilation of the work station. |
| Hand protection                  | : Protective gloves.                           |
| Eye protection                   | : Safety glasses.                              |
| Skin and body protection         | : Wear suitable protective clothing.           |
| Respiratory protection           | : Wear respiratory protection.                 |
| Environmental exposure controls  | : Avoid release to the environment.            |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|  |                         |
|--|-------------------------|
| Physical state                             | : Liquid                |
| Colour                                     | : red                   |
| Odour                                      | : characteristic        |
| Odour threshold                            | : No data available     |
| pH   | : No data available     |
| Melting point                              | : Not applicable        |
| Freezing point                             | : No data available     |
| Boiling point                              | : No data available     |
| Flash point                                | : >= 200 °C COC minimum |
| Relative evaporation rate (butylacetate=1) | : No data available     |
| Flammability (solid, gas)                  | : Not applicable.       |
| Vapour pressure                            | : No data available     |
| Relative vapour density at 20 °C           | : No data available     |
| Relative density                           | : No data available     |
| Density                                    | : 0.852 typical         |
| Solubility                                 | : No data available     |
| Log Pow                                    | : No data available     |
| Auto-ignition temperature                  | : No data available     |
| Decomposition temperature                  | : No data available     |
| Viscosity, kinematic                       | : 34 cSt @ 40 C typical |
| Viscosity, dynamic                         | : No data available     |
| Explosive limits                           | : No data available     |
| Explosive properties                       | : No data available     |
| Oxidising properties                       | : No data available     |

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

# Transmission Stop Leak

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Oxidizing agent.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

| <b>Glycol Ether DPM (34590-94-8)</b> |   |
|--------------------------------------|---|
| LD50 oral rat                        | 5135 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg; Rat; Experimental value)             |
| LD50 dermal rat                      | 9500 mg/kg (Rat; Literature study; Equivalent or similar to OECD 402; >19020 mg/kg bodyweight; Rat; Experimental value) |
| LD50 dermal rabbit                   | 9500 mg/kg (Rabbit; Literature study)   |
| ATE US (oral)                        | 5135.000 mg/kg bodyweight   |
| ATE US (dermal)                      | 9500.000 mg/kg bodyweight   |

| <b>Arylamine (90-30-2)</b> |   |
|----------------------------|---|
| LD50 oral rat              | 1625 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value) |

| <b>150 Neutral Base Oil (64742-58-1)</b> |              |
|--|--------------|
| LD50 oral rat                            | > 5000 mg/kg |

| <b>Xylene (1330-20-7)</b>  |   |
|----------------------------|---|
| LD50 oral rat              | 3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value) |
| LD50 dermal rabbit         | > 4200 mg/kg bodyweight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)   |
| LC50 inhalation rat (mg/l) | 29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)  |

| <b>Ethylbenzene (100-41-4)</b> |  |
|--------------------------------|--|
| LD50 oral rat                  | 3500 mg/kg (Rat; Other; Experimental value)  |
| LD50 dermal rabbit             | 15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value) |
| LC50 inhalation rat (mg/l)     | 17.8 mg/l/4h (Rat; Literature study)   |
| LC50 inhalation rat (ppm)      | 4000 ppm/4h (Rat; Literature study)  |
| ATE US (oral)                  | 3500.000 mg/kg bodyweight  |
| ATE US (dermal)                | 15415.000 mg/kg bodyweight   |
| ATE US (gases)                 | 4000.000 ppmv/4h   |
| ATE US (vapours)               | 17.800 mg/l/4h   |
| ATE US (dust,mist)             | 1.500 mg/l/4h  |

| <b>Toluene (108-88-3)</b>  |   |
|----------------------------|---|
| LD50 oral rat              | > 2000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value) |
| LD50 dermal rabbit         | 12223 mg/kg (Rabbit; Literature study; Other; >5000 mg/kg bodyweight; Rabbit; Experimental value)                       |
| LC50 inhalation rat (mg/l) | > 20 mg/l/4h (Rat; Literature study)  |

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified

# Transmission Stop Leak

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Not classified

| <b>Xylene (1330-20-7)</b>      |                                      |
|--------------------------------|--------------------------------------|
| IARC group                     | 3 - Not classifiable                 |
| <b>Ethylbenzene (100-41-4)</b> |                                      |
| IARC group                     | 2B - Possibly carcinogenic to humans |
| <b>Toluene (108-88-3)</b>      |                                      |
| IARC group                     | 3 - Not classifiable                 |

Reproductive toxicity : May damage fertility or the unborn child.

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

| <b>Glycol Ether DPM (34590-94-8)</b> |  |
|--------------------------------------|--|
| EC50 Daphnia 1                       | 1919 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)                   |
| Threshold limit algae 1              | 969 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum; Static system; Fresh water; Experimental value)   |
| Threshold limit algae 2              | > 969 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum; Static system; Fresh water; Experimental value) |

| <b>Arylamine (90-30-2)</b> |  |
|----------------------------|--|
| LC50 fish 1                | 0.44 mg/l (LC50; US EPA; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value) |
| EC50 Daphnia 1             | 0.3 mg/l (EC50; US EPA; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)         |
| Threshold limit algae 1    | >= 0.25 mg/l (EC50; 72 h)  |

| <b>Ethylbenzene (100-41-4)</b> |  |
|--------------------------------|--|
| LC50 fish 2                    | 4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value) |

### 12.2. Persistence and degradability

| <b>Glycol Ether DPM (34590-94-8)</b> |  |
|--------------------------------------|--|
| Persistence and degradability        | Readily biodegradable in water. No (test)data on mobility of the substance available. Photolysis in the air. |
| Biochemical oxygen demand (BOD)      | 0 g O <sub>2</sub> /g substance  |
| ThOD                                 | 2.06 g O <sub>2</sub> /g substance   |
| BOD (% of ThOD)                      | 0  |

| <b>Arylamine (90-30-2)</b>    |   |
|-------------------------------|---|
| Persistence and degradability | Not readily biodegradable in water. Low potential for mobility in soil. |

| <b>Xylene (1330-20-7)</b>     |   |
|-------------------------------|---|
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air. |

| <b>Ethylbenzene (100-41-4)</b> |  |
|--------------------------------|--|
| Persistence and degradability  | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil. |

# Transmission Stop Leak

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Ethylbenzene (100-41-4)</b>  |   |
|---------------------------------|---|
| Biochemical oxygen demand (BOD) | 1.44 g O <sub>2</sub> /g substance (20d.) |
| Chemical oxygen demand (COD)    | 2.1 g O <sub>2</sub> /g substance         |
| ThOD                            | 3.17 g O <sub>2</sub> /g substance        |
| BOD (% of ThOD)                 | 45.4 (20 days)                            |

| <b>Toluene (108-88-3)</b>       |  |
|---------------------------------|--|
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil. |
| Biochemical oxygen demand (BOD) | 2.15 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)    | 2.52 g O <sub>2</sub> /g substance   |
| ThOD                            | 3.13 g O <sub>2</sub> /g substance   |
| BOD (% of ThOD)                 | 0.69   |

### 12.3. Bioaccumulative potential

| <b>Glycol Ether DPM (34590-94-8)</b> |   |
|--------------------------------------|---|
| Log Pow                              | 0.0043 (Experimental value; OECD 102: Melting Point/Melting Range; 25 °C) |
| Bioaccumulative potential            | Low potential for bioaccumulation (Log Kow < 4).                          |

| <b>Arylamine (90-30-2)</b> |  |
|----------------------------|--|
| BCF fish 1                 | 427 - 2730 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 56 days; Cyprinus carpio; Flow-through system; Fresh water; Experimental value) |
| Bioaccumulative potential  | Potential for bioaccumulation (500 ≤ BCF ≤ 5000).  |

| <b>Xylene (1330-20-7)</b> |  |
|---------------------------|--|
| BCF fish 2                | 7 - 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water) |
| Log Pow                   | 3.2 (Conclusion by analogy; 20 °C)   |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500).                               |

| <b>Ethylbenzene (100-41-4)</b> |  |
|--------------------------------|--|
| BCF fish 1                     | 1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study) |
| BCF fish 2                     | 15 - 79 (BCF)  |
| BCF other aquatic organisms 1  | 4.68 (BCF)   |
| Log Pow                        | 3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)  |
| Bioaccumulative potential      | Low potential for bioaccumulation (BCF < 500).   |

| <b>Toluene (108-88-3)</b> |  |
|---------------------------|--|
| BCF fish 2                | 90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water) |
| Log Pow                   | 2.73 (Experimental value; Other; 20 °C)                    |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500).             |

### 12.4. Mobility in soil

| <b>Arylamine (90-30-2)</b> |  |
|----------------------------|--|
| Log Koc                    | log Koc,Other; 3.227; Calculated value |

| <b>Xylene (1330-20-7)</b> |   |
|---------------------------|---|
| Ecology - soil            | May be harmful to plant growth, blooming and fruit formation. |

| <b>Ethylbenzene (100-41-4)</b> |  |
|--------------------------------|--|
| Surface tension                | 0.029 N/m  |
| Log Koc                        | log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value |

| <b>Toluene (108-88-3)</b> |                  |
|---------------------------|------------------|
| Surface tension           | 0.03 N/m (20 °C) |

### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

# Transmission Stop Leak

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

GWPmix comment : No known effects from this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Not applicable

#### TDG

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Transmission Stop Leak

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Glycol Ether DPM (34590-94-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Mineral oil (64742-53-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Arylamine (90-30-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### 150 Neutral Base Oil (64742-58-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ

100 lb

##### Ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ

1000 lb

##### Toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ

1000 lb

#### 15.2. International regulations

##### CANADA

No additional information available

##### EU-Regulations

No additional information available



# Transmission Stop Leak

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### National regulations

#### Ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

#### Ethylbenzene (100-41-4)

|   |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| Yes   | No  | No  | No  | 54                                |

#### Toluene (108-88-3)

|   |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | Yes   | Yes   | Yes   | 7000                              |

#### Glycol Ether DPM (34590-94-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

#### Xylene (1330-20-7)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### Ethylbenzene (100-41-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### Toluene (108-88-3)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Revision date : 11/02/2016

Full text of H-statements:


|      |   |
|------|---|
| H225 | Highly flammable liquid and vapour                                |
| H226 | Flammable liquid and vapour                                       |
| H227 | Combustible liquid  |
| H302 | Harmful if swallowed  |
| H304 | May be fatal if swallowed and enters airways                      |
| H312 | Harmful in contact with skin                                      |
| H315 | Causes skin irritation  |
| H317 | May cause an allergic skin reaction                               |
| H332 | Harmful if inhaled  |
| H336 | May cause drowsiness or dizziness                                 |
| H360 | May damage fertility or the unborn child                          |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life  |
| H401 | Toxic to aquatic life   |
| H402 | Harmful to aquatic life   |
| H410 | Very toxic to aquatic life with long lasting effects              |
| H412 | Harmful to aquatic life with long lasting effects                 |

# Transmission Stop Leak

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
- NFPA fire hazard : 1 - Must be preheated before ignition can occur.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



- HMIS III Rating
- Health : 1 Slight Hazard - Irritation or minor reversible injury possible
- Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
- Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
- Personal protection : B  
B - Safety glasses, Gloves

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*