

2





BARDAHL SPECIAL DUTY

Power Booster

Extra protection for severe service conditions such as Trailer towing, Air cooled engines, hot weather driving, heavy-duty truck & trailer.

The problem

Hard working engines in trailer-towing, off-road or recreational vehicles demand extra protection from the engine oil to maintain efficiency and performance. Heavy loads and high temperature operation will break down the active ingredients in motor oil. This will result in lower oil pressure, increased oil consumption, greater friction, more wear and the formation of harmful engine deposits. The depletion of these important oil properties will reduce performance and can lead to serious engine damage and costly repairs.

THE SOLUTION

BARDAHL Special Duty is an ultra concentrated formula that reduces engine wear, restores lost power and increases engine efficiency. The formulation uses 'polar attraction' compounds to enhance the level of lubrication. Engine Power Booster is comprised of anti-wear, extreme pressure, and oxidation inhibiting additives, plus an oil stabilizer to improve the strength and thickness of the oil film at high tem-

peratures, providing the essential level of protection for hard working gasoline and diesel engines.

The benefits

- Excellent for commercial vehicles and severe service conditions
- Maintains peak engine performance
- Reduces friction and wear
- Increases mileage
- Quiets hydraulic lifter noise
- Improves power and performance in older engines
- Protects against excessive oil temperatures



DIRECTIONS

Add one part Bardahl Special Duty to four parts of oil at each oil change (20%). Pour contents into cranckcase of warm, idling engine. Add betweens oil changes as needed. Do Not overfill crankcase. Compatibles with all motor oils. Dispose of any used or unused solution in accordance with local, state, and federal regulations.

Product Specifications	
Product #	1532
Unit UPC#	0 76906 01532 5
Case UPC#	30076906015326
Pack Size	24x32oz (.946 mL)
Dimensions	L x 16.5" W x 12.5" H 11.5"
Weight & Cubic ft ³	51 lbs / 1.37 ft ³
Color	Amber
Specific Gravity	0.900
Viscosity	80 cSt @ 100°C
Flash Point	>000°F / >000°C