

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 12/21/2023 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : Gas Plus
Product code : 3003

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Gasoline additive

1.3. Supplier

Bardahl Manufacturing Corporation 1400 NW 52nd Street P.O. Box Seattle, WA 98107 USA T 206-783-4851 - F 206-784-3219

www.bardahl.com
Contact: Jackie Leung

1.4. Emergency telephone number

Emergency number : 800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids, Category 4 Skin corrosion/irritation, Category 2 Germ cell mutagenicity, Category 1B Carcinogenicity, Category 1B Aspiration hazard, Category 1

Hazardous to the aquatic environment – Chronic Hazard, Category 2

Combustible liquid
Causes skin irritation.
May cause genetic defects.

May cause cancer.

May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Hazard statements (GHS US) : Combustible liquid

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause genetic defects.

May cause cancer.

Toxic to aquatic life with long lasting effects.

Precautionary statements (GHS US) : Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Wash hands thoroughly after handling.

Avoid release to the environment.

Wear eye protection, protective gloves.

If swallowed: Immediately call a poison center or doctor.

If on skin: Wash with plenty of water.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see supplemental first aid instruction on this label).

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use alcohol resistant foam, BC-powder, carbon dioxide (CO2) to extinguish.

Collect spillage.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Petroleum distillates (Diesel fuel no. 2)	CAS-No.: 68476-34-6	≥ 80	Flam. Liq. 4, H227 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Solvent naphtha (light aromatic)	CAS-No.: 64742-95-6	1 – 5	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 3, H402
Dipropylene glycol monomethyl ether	CAS-No.: 34590-94-8	1 – 5	Flam. Liq. 4, H227 STOT SE 3, H335
Polyolefin alkyl phenol alkyl amine	CAS-No.: Confidential	0.1 – 5	Skin Irrit. 2, H315
Cumene	CAS-No.: 98-82-8	0.01 – 1	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable

protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

12/21/2023 (Issue date) EN (English) 3/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures

Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Cumene (98-82-8)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 ppm	
Dipropylene glycol monomethyl ether (34590-94-8)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	CGIH OEL TWA 50 ppm	
USA - OSHA - Occupational Exposure Limits		
Local name	Dipropylene glycol methyl ether	
OSHA PEL TWA	600 mg/m³	
	100 ppm	
Petroleum distillates (Diesel fuel no. 2) (68476-34-6)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Diesel fuel as total	
ACGIH OEL TWA	100 mg/m³	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

: Colourless amber Colour Odour : characteristic Odour threshold : No data available рΗ : No data available : Not applicable Melting point Freezing point : No data available Boiling point No data available Flash point 62.2 °C PMCC typical Relative evaporation rate (butylacetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapour pressure : No data available Relative vapour density at 20°C : No data available Relative density : No data available Density : 0.838 g/cm³ typical Solubility No data available Partition coefficient n-octanol/water (Log Pow) : No data available No data available Auto-ignition temperature

Viscosity, kinematic : 2.7 mm²/s @ 40 C typical Viscosity, dynamic : No data available

Explosive limits : No data available
Explosive properties : No data available
Oxidising properties : No data available

9.2. Other information

Decomposition temperature

No additional information available

No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation)	: Not classified	
Solvent naphtha (light aromatic) (64742-95-	6)	
LD50 oral rat	> 2000 mg/kg (Rat, Oral)	
LD50 dermal rabbit	> 3160 mg/kg (Rabbit, Dermal)	
Cumene (98-82-8)		
LD50 oral rat	2700 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 014 day(s))	
LD50 dermal rabbit	> 3160 mg/kg bodyweight (24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))	
LC50 Inhalation - Rat	39 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s))	
ATE US (oral)	2700 mg/kg bodyweight	
ATE US (vapours)	39 mg/l/4h	
ATE US (dust,mist)	39 mg/l/4h	
Dipropylene glycol monomethyl ether (34590-94-8)		
LD50 oral rat	> 5000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))	
LD50 dermal rabbit	9510 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))	
ATE US (dermal)	9510 mg/kg bodyweight	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations			
Petroleum distillates (Diesel fuel no. 2) (68476-34-6)			
LD50 oral rat	> 5000 mg/kg (Rat, Oral)		
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)		
LC50 Inhalation - Rat	> 5 mg/l (4 h, Rat, Inhalation)		
ATE US (gases)	4500 ppmv/4h		
ATE US (vapours)	11 mg/l/4h		
ATE US (dust,mist)	1.5 mg/l/4h		
Skin corrosion/irritation :	Causes skin irritation.		
Cumene (98-82-8)			
рН	No data available in the literature		
Dipropylene glycol monomethyl ether (34590-	94-8)		
рН	7 (100 %)		
Serious eye damage/irritation :	Not classified		
Cumene (98-82-8)			
рН	No data available in the literature		
Dipropylene glycol monomethyl ether (34590-	94-8)		
рН	7 (100 %)		
'	Not classified		
	May cause genetic defects. May cause cancer.		
Cumene (98-82-8)	intay cadab cantoon.		
IARC group	2B - Possibly carcinogenic to humans		
,	Not classified		
- 5 1	Not classified		
Cumene (98-82-8)			
STOT-single exposure	May cause respiratory irritation.		
Dipropylene glycol monomethyl ether (34590-	94-8)		
STOT-single exposure	May cause respiratory irritation.		
	Not classified		
	May be fatal if swallowed and enters airways. 2.7 mm²/s @ 40 C typical		
Solvent naphtha (light aromatic) (64742-95-6)			
Viscosity, kinematic	0.785 mm²/s		
Cumene (98-82-8)			
Viscosity, kinematic	0.74 mm²/s (38 °C)		
Dipropylene glycol monomethyl ether (34590-	Dipropylene glycol monomethyl ether (34590-94-8)		
Viscosity, kinematic	4.55 mm²/s (20 °C, OECD 114: Viscosity of Liquids)		
Petroleum distillates (Diesel fuel no. 2) (68476	3-34-6)		
Viscosity, kinematic	3.3 (1.7 – 4.1) mm²/s @ 40 C		
Symptoms/effects after skin contact :	Irritation.		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Risk of lung oedema.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Solvent naphtha (light aromatic) (64742-95-6)	
LC50 - Fish [1]	18 mg/l (Pisces)
EC50 - Crustacea [1]	21 mg/l (Daphnia sp.)
Cumene (98-82-8)	
LC50 - Fish [1]	4.8 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	2.14 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	2.01 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
Dipropylene glycol monomethyl ether (34590-	94-8)
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	> 969 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

12.2. Persistence and degradability			
Gas Plus			
Persistence and degradability	Rapidly degradable		
Solvent naphtha (light aromatic) (64742-95-6)	Solvent naphtha (light aromatic) (64742-95-6)		
Persistence and degradability	Readily biodegradable in water.		
Cumene (98-82-8)			
Persistence and degradability	Readily biodegradable in water,Not easily biodegradable in water in anaerobic conditions.		
Biochemical oxygen demand (BOD)	1.28 g O ₂ /g substance		
Chemical oxygen demand (COD)	2.42 g O₂/g substance		
ThOD	3.2 g O ₂ /g substance		
Polyolefin alkyl phenol alkyl amine (Confidential)			
Persistence and degradability	Rapidly degradable		
Dipropylene glycol monomethyl ether (34590-94-8)			
Persistence and degradability	Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance		
ThOD	2.06 g O₂/g substance		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum distillates (Diesel fuel no. 2) (68476-34-6)	
Persistence and degradability	Inherently biodegradable.

12.3. Bioaccumulative potential

Solvent naphtha (light aromatic) (64742-95-6)		
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6	
Cumene (98-82-8)		
BCF - Fish [1]	94.69 l/kg (BCFBAF v3.00, Pisces, Fresh weight)	
Partition coefficient n-octanol/water (Log Pow)	3.55 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 23 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Dipropylene glycol monomethyl ether (34590-94-8)		
Partition coefficient n-octanol/water (Log Pow)	0.004 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Petroleum distillates (Diesel fuel no. 2) (68476-34-6)		
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6	

12.4. Mobility in soil

Cumene (98-82-8)		
Surface tension	28.2 mN/m (20 °C)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.9 (log Koc, Calculated value)	
Ecology - soil	Low potential for adsorption in soil.	
Dipropylene glycol monomethyl ether (34590-94-8)		
Surface tension	68.7 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil. Not toxic to plants.	
Petroleum distillates (Diesel fuel no. 2) (68476-34-6)		
Surface tension	25 mN/m	
Ecology - soil	No (test)data on mobility of the component(s) available.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

12/21/2023 (Issue date) EN (English) 9/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA No : Not regulated UN-No. (TDG) : Not applicable UN-No. (IMDG) : Not applicable UN-No. (IATA) : Not regulated

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not regulated

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not regulated

TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not regulated

14.4. Packing group

Packing group (DOT): Not regulatedPacking group (TDG): Not applicablePacking group (IMDG): Not applicablePacking group (IATA): Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

Not regulated

TDG

Not applicable

IMDG

Not applicable

IATA

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Solvent naphtha (light aromatic)	64742-95-6	Present	Active	
Cumene	98-82-8	Present	Active	
Polyolefin alkyl phenol alkyl amine	Confidential	Not present	-	
Dipropylene glycol monomethyl ether	34590-94-8	Present	Active	
Petroleum distillates (Diesel fuel no. 2)	68476-34-6	Present	Active	

Cumene (98-82-8)

Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 5000 lb

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

Cumene (98-82-8)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Cumene (98-82-8)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
Cumene(98-82-8)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Dipropylene glycol monomethyl ether(34590-94-8)	U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary

incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

: 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

NFPA reactivity

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II IIIA)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

: B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

Personal protection

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.