



TECH REPORT



The Original Bardahl USA

XTC 0W-20 SYNTHETIC MOTOR OIL

Specifications: API SP-RC

ProductNo(s): 22600-22606

Product Description

XTC 100% SYNTHETIC 0W-20 is a high performance passenger car engine oil designed to meet the latest car manufacturers warranty requirements. Specifically formulated to meet the demands of the small displacement high RPM fuel efficient engines found in today's domestic and foreign automobiles.

The oil is a blend of the synthetic premium base oils and special additives which protect against high temperature oxidation, wear, and viscosity breakdown. It is fortified with detergent-dispersants, rust and corrosion inhibitors and friction modifiers to keep engines exceptionally clean and free of sludge, varnish, rust and meet the fuel economy requirements. It meets the performance of API SP-RC & SNPLUS, ILSAC GF-6A



Advantages & Uses

- Meets RC requirements and is recommended for domestic and foreign high performance engines. It is recommended for small, high RPM engines including those that are turbo-charged.
- Recommended for passenger cars, light duty pickups, motorcycles and other gasoline engines in mobile and stationary service.
- Appropriate viscosity grades meet the warranty requirements of Chrysler, Ford Motor Co., and General Motors specifications.

Features

- Highly oxidation stable - protects engine from oil thickening, high temperature sludge and varnish deposits.
- Shear stable viscosity index improver-protects against viscosity breakdown in severe service.
- Effective detergent-dispersants keeps engine parts clean.
- Improved fuel economy means better gasoline mileage.
- High TBN / alkaline reserve effectively neutralizes corrosive acids formed by combustion to protect critical turbo charger bearings and other vital engine surfaces.
- Anti-wear agents effectively protect cam lobes and other highly loaded parts from wear.

Typical Specifications

TEST	ASTM	Result
Gravity, °API	D-287	32.5
Flash Point, °C	D-92	230
Pout Point, °C	D-97	-40
Viscosity: cSt @ 100 °C	D-445	8.0
Viscosity: cSt @ -30 °C	D-5293	5,400
Viscosity Index	D-2270	159
Apearance	Visual	Bright & Clear
Color	D-1500	3.0
Zinc, Wt. %	D-5185	0.085
Phos, Wt. %	D-5185	0.077
TBN	D-2896	7.9

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY